

# V-RECON SERIES VP-FDNC27X-E

High Speed Eco Dome PTZ Camera



\*Mount is not included



## Key Features

- 27x Optical Power Zoom Lens, 10x Digital Zoom (Max. 270x)
- Pan: 360 at maximum speed of 150 /sec
- Tilt: 0~ 90 at maximum speed of 120/sec
- Auto switch function with 30 preset positions
- Built-in OSD Menu, to change dome parameter, save or call preset, and achieve auto scan, pattern etc
- Password protection to prevent unauthorized changes to the dome setting
- The feature of defining specific activity when the dome parks
- Auto-flip to follow object and surveillance of any subject that is constant and continuous
- Auto focus lens and auto white balance, BLC function
- Multi protocol compatible (Pelco- D/P)
- Reinforced inside components

Specifications	VP-FDNC27-E
<b>Sensor</b>	1/4" IT CCD
<b>Signal System</b>	NTSC / PAL
<b>Max Pixels</b>	811 (H) x 508 (V) 410K (NTSC) 795(H) x 596(V) 470K (PAL)
<b>Effective Pixels</b>	768 (H) x 494 (V) 380K (NTSC) 752(H) x 582(V) 440K (PAL)
<b>Min. Illumination</b>	0.5Lux (Day) (30IRE) / 0.1Lux (30IRE) (Night) / DSS 0.0005Lux (128FLD, 30IRE)
<b>Digital Zoom</b>	10x
<b>Day and Night</b>	Auto
<b>Lens</b>	27x Zoom Video AF (f=3.6~97.2mm, F1.6(W)- F3.7(T))
<b>Video Output Level</b>	1.0Vp-p/75 Ω
<b>Horizontal Resolution</b>	600 TV Lines (BW 700 TV Lines)
<b>Automatic Gain Control (AGC)</b>	On/Off
<b>Back Light Compensation (SBack Light Compensation)</b>	Zone Selectable
<b>DSS</b>	Off/2FLD~128FLD Mode
<b>3D-DNR</b>	Low/Middle/High
<b>Pan/Tilt Range</b>	Pan: 360° continuous Tilt: 0°~90° auto flip
<b>Pan/Tilt Speed</b>	Pan: 0.05° ~ 150°/sec Tilt: 0.03°~120°/sec
<b>Presets</b>	256
<b>Pattern</b>	4 routes of pattern
<b>Auto Cruise</b>	Auto switch from 1 to 30 preset positions sequentially
<b>Communication Port</b>	RS-485
<b>Baud rate</b>	1200 / 2400 / 4800 / 9600 / 19200 bps
<b>Address</b>	0~255
<b>S/N</b>	More than 50dB(AGC off)
<b>ENVIRONMENTAL</b>	
<b>Temperature</b>	32°F ~ 129.2°F (0°C ~ +54°C)
<b>ELECTRICAL</b>	
<b>Power Supply</b>	24VDC/24VAC (12Volt Special Order)
<b>PHYSICAL</b>	
<b>Unit Weight</b>	3Lb + Mount weight

## Recommended Accessories



W6  
(Outdoor)  
11lb (5Kg)

P6  
(Pendant)  
9lb (4Kg)

VM-POLE  
(Pole)  
8lb (3.62Kg)

VM-CORNER  
(Corner)  
9lb (4Kg)