

V-RECON SERIES VS-70 / VS-70T

High Resolution Day & Night Standard Box Camera



Specifications	VS-70 / VS-70T
Sensor	1/3" Sony EFFIO-V 960H CCD
Signal System	NTSC / PAL
Effective Pixels	1020(H) x 508(V) (NTSC) 1020(H) x 596(V) (PAL)
Sync. System	Internal LL (phase adjustable power supply)
Min. Illumination	0.01Lux
Horizontal Resolution	Over 760TVL
Noise Reduction	3DNR + 2DNR
Video Output Level	1.0Vp-p/75 Ω
S/N	>52dB (AGC off)
Gain Control	Auto
BLC	BLC / HLC
WDR	Super WDR
Electronic Shutter	Auto / Manual / Fixed
White Balance	AWB (1800K-10500K)
White Pixel Detection Compensation	Static and Dynamic
Image Adjustable	Brightness/Contrast/Saturation/Sharpness/Mirror
ENVIROMENTAL	
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% -85% RH
ELECTRICAL	
Power Supply	VS-70 12 VDC VS-70T 12VDC/24VDC/24VAC
Power Consumption	Less than 150mA
PHYSICAL	
Dimensions (W x D x H)	2.3" x 3.9" x 2.5" [6cm x 10cm x 6.5cm]
Unit Weight	0.75 lb (0.340 kg)
Shipping Weight	0.95 lb (0.430 kg)



Key Features

- Triple Voltage Optional (12VDC, 24VDC, 24VAC)
- Digital Zoom
- Defog
- Digital Image Stabilizer
- AF Detector
- Lens Shading Compensation
- Motion Detection
- Sense Up
- Privacy Zone Mask
- WDR more than 100dB
- Video Signal-to-Noise >52 dB

Recommended Accesories



Outdoor/Indoor Camera Housing

- VCH-619
- VCH-619HB
- VCH-619HBIR



Lens

- VL-1.6MP



- VPS-12810
- VPS-121630