

V-RECON SERIES VV-13IR36V

Analog 1.3 Megapixel Vandal Proof IR Dome Camera



Specifications	VV-13IR36V
Sensor	Color 1/3" SONY DIS
Signal System	NTSC / PAL
Max Pixels	1280H x 1024V (at 30FPS)
Effective Pixels	976(H) x 494(V) (NTSC) 976(H) x 582(V) (PAL)
Min.. Illumination	0.001Lux@F1.2 (Color) (0 Lux IR LED ON)
IR LED	36 Units
Night View Distance	Indoor 35m/Outdoor 25m
Lens	2.8-12mm Auto Iris Varifocal
Video Output Level	1.0Vp-p/75 Ω
Horizontal Resolution	1.3 Megapixel 720P (more than 1000 TVL)
S/N	More than 52dB(AGC off)
White Balance	ATW / AWC / MANUAL / PUSH
Viewing Angle	Wide: 76.1° x 55.8° (HxV) Tele 23.8° x 17.9° (HxV)
ENVIROMENTAL	
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% -85% RH
IP Rating	IP68
ELECTRICAL	
Power Supply	12 VDC
Power Consumption	Less than 150mA
PHYSICAL	
Dimensions (W x D x H)	Ø2.75" x 11.4"(D) [Ø7cm x 29cm(D)]
Unit Weight	1.65 lb (0.748 kg)
Shipping Weight	2.10 lb (0.952 kg)



Key Features

- Automatic Sensor-up function
- S/N ratio more than 52dB (AGC Off)
- No ghosting when moving
- Excellent pixel technology
- The lowest random noise
- Stable black level and long endurance
- OSD
- BLC (Black Light Compensation)
- WDR more than 100dB
- Synchronization LL (phase adjustable power supply synchronization)

Recommended Accessories



- VPS-12810
- VPS-121630